


**Physical Address:**

CRANE Instrumentation & Sampling
 405 Centura CT,
 Spartanburg, SC 29303-6603
 Phone: (864) 574-7966
 Fax: (864) 587-5608
 Email: [Click Here](#)

Mailing Address:

HOKE
 PO Box 4866,
 Spartanburg, SC 29305-4866

Item # CVH K 12 Y 1 1 S, Female British Parallel Pipe, (Fractional)



Specifications

Fitting Size	3/4"/12mm
Body Material	316 Stainless Steel
Crack Pressure	0.5 psig (0.04 bar)
Seal Material	Viton
Cv Factor	7.38
Temperature	-20° to +400° °F -29° to +204° °C
A	1.17 in
B	1.51 in
C	1.51 in
D	4.19 in
E	0.66 in

F

2.25 in

Features & Specifications

- Rapid response
- Resilient o-ring seat provides cushioned, noise-free closing and zero leakage
- Floating o-ring design: o-ring is continually cleaned so contaminants do not prevent sealing
- Various materials of construction can be used with any liquid or gas service
- Various end connections can be assembled in any system or application
- Spring-loaded poppet can be mounted in any orientation
- Full flow with minimal restriction for maximum Cv rates
- Virtually maintenance free for maximum dependability
- Pressures up to 6000 psig (414 bar)
- Cracking pressure range is 0.5 to 20 psig (0 to 1 bar) ±10%
- Flow up to 7.4 Cv maximum
- Greater than 100,000 life cycles
- Special High Tolerance NPT Thread